Worktop Oil

For Kitchen Worktops & Joinery

This high-performance wood oil is expertly designed for worktops and tables, offering superior nourishment and protection. It delivers a high quality finish that effectively resists spills, stains, and scratches from everyday use with the benefit of being certified Food & Toy safe. Suitable for all types of solid wood and premium veneers, it naturally enhances the wood's rich tones, ensuring long-lasting protection without peeling or flaking. Treated surfaces are easy to maintain and should any damage occur it is easily spot repaired.

Preparation: For freshly laid wood, allow to acclimatise in the room for several days before treating. Moisture content should be below 15%. Previous coatings must be fully sanded back before application. Resinous deposits should be removed with a scraper and the surface degreased, with methylated spirits. Repair cracks or open joints with a suitable wood filler. Use 120-150 grit sandpaper to achieve a smooth surface on the wood. Remove any sanding dust thoroughly before application. If required, apply wood dye.

IMPORTANT! Test the colour and compatibility with any wood fillers or dyes on a scrap piece of wood before use.

Coverage: Approximately 24-28 m^2/l (One Coat), 12-16 m^2/l (Two Coats), depending on substrate absorbency and smoothness.

Application: Read entire label and carry out a test patch before starting any project. Ensure good ventilation is maintained during application and throughout the drying process. Ready to use, do not thin.

Stir thoroughly before use. Decant into a paint kettle/scuttle and apply in thin coats using a short pile roller, good quality brush or lint free cloth. Over-application can reduce the finish quality and prolong drying time. Two coats recommended on bare wood, second/maintenance coats best applied by wiping with a cloth.

Drying Time: Touch dry in 4 hours under average climatic conditions (23°C, 50% humidity). Preferably allow to dry overnight. Variations in ambient conditions and substrate can affect drying times.

Equipment Cleaning: Clean brushes / rollers with Barrettine White Spirit immediately after use. If spilled, wipe off immediately with a cloth dampened with Barrettine White Spirit.

Precaution: Cloths used for oiling could, under certain conditions, self-combust. Immediately after use, soak them in soapy water then lay them flat outside on a non-combustible surface to dry.

Maintenance: Marks and scratches can be touched up without the requirement for sanding. Ensure areas to be repaired are clean and dry. To renovate large areas lightly sand with 120-150 grit sandpaper, remove dust and then apply a single, thin coat. ArmourFlex® Worktop Oil imparts a tough, resilient surface to the wood that resists typical daily wear and tear. To help retain the best appearance a good level of general care is advised. Clean surfaces with a none abrasive pH balanced cleaner such as Armourflex Wood Surface Cleaner and avoid scouring with abrasive creams or sponges.

Storage advice: Store upright and in a cool frost-free area between 5-30°C.

Health, Safety & Environmental Information: Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist, vapours, spray. Use only outdoors or in a well-ventilated area. Call a POISON CENTER, doctor if you feel unwell. Store locked up. Dispose of contents and container to a hazardous or special waste collection point.

EU limit value for this product (Cat. A/i): 500g/l (2010). This product contains max 475g/l VOC.

Warning

Barrettine Products Ltd:
St. Ivel Way, Warmley, Bristol. BS30 8TY. UK
T: +44 (0) 117 9600060
E: sales@barrettine.co.uk
www.barrettinePro.co.uk

Barrettine (Europe) Ltd:
Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork. T23 AT2P. Ireland.
T: +353 21 206 6530

Barrettine
TRUSTED BY THE PROFESSIONALS

ArmourFlex®
• Hard-wearing • Flexible • Protection

Worktop Oil

For Kitchen Worktops & Joinery

4 hr DRYING TIME

Tough, Durable and Water Repellent

Manufactured in the UK

- ✓ Stain, Dirt & High Scratch Resistance
- ✓ Natural Oil / Waxed Based
- ✓ Certified Food & Toy Safe
- ✓ 4 Hour Drying Time

FOOD & TOY SAFE A B — EN1186:2002 EN71:3

ABRASION RESISTANT — ISO 7786

LIQUID RESISTANT — ISO 2812-1

CLEAR
MATT

500ml

5 015861 006875

UFI: 0S90-K0AW-J000-TM4H