

Barrettine
TRUSTED BY THE PROFESSIONALS

ArmourFlex

• Hard-wearing • Flexible • Protection




Hardwax Oil

For Wooden Floors & Furniture

4 hr
DRYING
TIME

Tough, Durable and Water Repellent

Manufactured in the UK 

- ✓ Stain, Dirt & High Scratch Resistance
- ✓ Natural Oil / Waxed Based
- ✓ Certified Food & Toy Safe
- ✓ 4 Hour Drying Time



EN1186:2002
EN71:3



ISO 7786



ISO 2812-1

CLEAR

MATT



Overview: Armourflex® Hardwax Oil for wooden floors, stairs, kitchen worktops & furniture is a specialist high performance coating that offers an outstanding finish with exceptional wear characteristics and is certified Food & Toy Safe when dry to EN 1186:2002 & EN71:3. Containing a blend of natural oils and waxes it is suitable for protecting and enhancing the natural beauty of all interior wood surfaces including hardwood, softwood, parquet and veneer. Treated surfaces are easy to maintain and should any damage occur it is easily spot repaired.

Preparation

For freshly laid wood, allow to acclimatise in the room for several days before treating. Moisture content should be below 15%. Previous coatings must be fully sanded back before application. Resinous deposits should be removed with a scraper and the surface degreased, with methylated spirits. Repair cracks or open joints with a suitable wood filler. Use 120-150 grit sandpaper to achieve a smooth surface on the wood. Remove any sanding dust thoroughly before application. If required, apply wood dye.

IMPORTANT! Test the colour and compatibility with any wood fillers or dyes on a scrap piece of wood before use.

Coverage

Approximately 24-28 m²/l (One Coat), 12-16 m²/l (Two Coats), depending on substrate absorbency and smoothness.

Application: Read entire label and carry out a test patch before starting any project. For detailed instructions please visit: www.barrettinepro.co.uk

Ensure good ventilation is maintained during application and throughout the drying process. Ready to use, do not thin.

Stir thoroughly before use. Apply in thin coats using a short pile roller, good quality brush or lint free cloth. Over-application can reduce the finish quality and prolong drying time. Two coats recommended on bare wood, second/maintenance coats best applied by wiping with a cloth.

Drying Time

4 hours under average climatic conditions (23°C, 50% humidity). Preferably allow to dry overnight. Variations in ambient conditions and substrate can affect drying times. Suitable for light foot traffic approximately 16 hours after final coat.

Equipment Cleaning

Clean brushes / rollers with Barrettine White Spirit immediately after use. If spilled, wipe off immediately with a cloth dampened with Barrettine White Spirit.

Precaution: Cloths used for oiling could, under certain conditions, self-combust. Immediately after use, soak them in soapy water then lay them flat outside on a non-combustible surface to dry.

Maintenance

Marks and scratches can be touched up without the requirement for sanding. Ensure areas to be repaired are clean and dry. To renovate large areas lightly sand with 120-150 grit sandpaper, remove dust and then apply a single, thin coat. ArmourFlex® Hardwax Oil imparts a tough, resilient surface to the wood that resists typical daily wear and tear. To help retain the best appearance a good level of general care is advised e.g., avoiding dragging heavy items like furniture and keeping pet claws regularly trimmed.

Cleaning

Vacuum or sweep the floor regularly to remove loose dirt from the surface and avoid scratches. Wipe up any spills immediately. Never steam clean or saturate floor with water to clean, this may reduce the service life and cause damage to the wood below. Floors should be regularly cleaned with a light spray of Wood Floor Cleaner and a microfibre mop. **Storage advice:** Store upright and in a cool frost-free area between 5-30°C

Health, Safety & Environmental Information

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics.

Flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist, vapours, spray. Use only outdoors or in a well-ventilated area. Call a POISON CENTER, doctor if you feel unwell. Store locked up. Dispose of contents and container to a hazardous or special waste collection point.

EU limit value for this product (Cat. A/I): 500g/l (2010).

This product contains max 475g/l VOC.



Warning

LEARN MORE



UFI: OS90-KOAW-J000-TM4H

1 litre

Barrettine (Europe) Ltd.
Unit 3D North Point House,
North Point Business Park,
New Mallow Road,
Cork, T23 AT2P, Ireland.

T: +353 21 206 6530

Barrettine
TRUSTED BY THE PROFESSIONALS

Barrettine Products Ltd.
St. Ivel Way, Warmley,
Bristol, BS30 8TY, UK.

T: +44 (0) 117 9600060

E: sales@barrettine.co.uk

www.barrettinepro.co.uk